




Range Comparison Chart




Exit Blades

Range	Summary	Viewing Distance	Pictographs	IP Rating	Lamp Life	Testing Function			Warranty
						Standard	Self-testing	Nexus LX / Nexus RF wireless	
 Economy	Cost-effective, entry-level solutions. Boxy style design.	24m	1	IP20	70,000 hours	✓			5 years
 ST Series	Value packed with self-testing technology and multiple mounting options.	24m	3	IP20	50,000 hours	✓	✓		3 years
 Platinum	High-spec, premium range with full picto range and monitoring options.	24m	3	IP20 or IP65	100,000 hours	✓		✓	5 years

Spitfires

Range	Summary	Lens	LED Type	Mount Type	Lamp Life	Testing Function			Warranty
						Standard	Self-testing	Nexus LX / Nexus RF wireless	
 Economy	Simple, reliable, and ideal for budget-conscious projects.	Supplied with single lens only	LED	Fixed type (Recessed or Surface)	100,000 hours	✓			5 years
 ST Series	Smart, packed with value, and built for convenience	Supplied with interchangeable lenses (open area and corridor)	COB LED	Dual-mount (Recessed + Surface in one)	50,000 hours	✓	✓		3 years
 Platinum	Durable, efficient, and built for long-term performance.	Supplied with single lens only	COB LED	Fixed type (Recessed or Surface)	100,000 hours	✓		✓	5 years

Floodlights

Range	Summary	Lumens	IP Rating	Photometrics	Mount Type	Testing Function			Warranty
						Standard	Self-testing	Nexus LX / Nexus RF wireless	
 Economy	Reliable option for internal areas, warehouses, and large open indoor spaces.	475	IP65	Good coverage	Wall	✓			5 years
 ST Series	Cost-effective, easy install ideal for car parks, warehouses, and outdoor egress areas.	630	IP65	Efficient output, excellent performance and value	Wall	✓	✓		3 years
 Platinum	Premium spec, for long life, lower maintenance, more rugged / weatherproof installations.	1080	IP65	Exceptional performance, maximum coverage	Wall	✓		✓	5 years

Stanilite® ST Series

Product Range



ST Weatherproof flood IP65 LED emergency self test

The Stanilite Flood, Smarter Than Ever.

The ST Weatherproof flood is built for performance under pressure. With a long life lithium iron phosphate battery and energy saving LED technology. Lightweight and weatherproof tough, it's smart emergency lighting with zero compromise.

Voltage	220-240V _{AC}
Mains frequency	50/60Hz
Mains power	3W max
Emergency power	0.7W
Commissioning test duration	120 min
Battery	LiFePO4 3.2V 1.5Ah
Discharge duration	90 min



ST Quick multifix LED exit self test

One Exit, Five Solutions. Smarter Safety.

The ST Quick multifix LED exit self test is engineered to outrun, combining self-testing intelligence with a 24m viewing range and energy-saving LED performance. Ceiling / Wall / Cantilever / Rod / Chain mounting options. (Cantilever kits sold separately)

Voltage	220-240V _{AC}
Mains frequency	50/60Hz
Mains power	3W max
Emergency power	0.7W
Commissioning test duration	120 min
Battery	LiFePO4 3.2V 1.5Ah
Discharge duration	90 min



ST Spitfire® LED self test

One spitfire, Two Lenses. Smarter Safety.

The ST Spitfire is a versatile emergency lighting solution featuring two interchangeable lenses that let you easily switch between corridor and open area coverage. With self-testing functionality, and a long-life lithium iron phosphate battery, it ensures reliable performance and quick installation.

Voltage	220-240V _{AC}
Mains frequency	50/60Hz
Mains power	2W max
Emergency power	2W
Commissioning test duration	120 min
Battery	LiFePO4 3.2V 3.3Ah
Discharge duration	90 min

Surface mount ready (kit sold separately).

